

CONTAINER & PALLET DOLLY



COD LD1xLD3 TT
 PAD 96"x125" TT
 PAD 96"x125" C

CONTAINER & PALLET DOLLY

Technical Specifications	COD LD1xLD3 TT	PAD 96"x125" TT	PAD 96"x125" C
Chassis	1760 x 2300 mm, hot dip galvanized	3550 x 2700 mm, hot dip galvanized	3282 x 2590 mm, hot dip galvanized
Loading Area	2300 x 1560 mm	3180 x 2500 mm	3200 x 2470 mm
Tow Length	3815 mm	5675 mm	4045 mm
ULD/Pallet Capability	LD1 / LD2 / LD3	96"x125" (PAG, PMC, PLA)	96"x125" (Extra locks optional)
Load Capacity	1800 kg	6800 kg	7000 kg
Rotation Method	Turntable, 360 °	Turntable, 360 °	Castor/Wheels, Front
Rollers	∅60mm, length 380mm, 2" thick, galvanized, 28 pieces along 3 rows	∅60mm, length 375mm, 2" thick, galvanized, 56 pieces along 4 rows	∅89mm, length 585mm, 3" thick, galvanized, 28 pieces along 2 rows
Tires	400 x 100 Solid	400 x 100 Solid	260x160 Solid (Front) 400 x100 Solid (Rear)
Brakes	Tow-bar activated brake-by-bar at 2 positions	Tow-bar activated brake-by-bar at 2 positions	Tow-bar activated brake-by-bar at 2 positions
Tow Speed	up to 30 km/h	up to 30 km/h	up to 30 km/h



COD LD1xLD3 TT



PAD 96"x125" TT



PAD 96"x125" C