

## *Streamline CargoMaster*

**Model HTLP (8,000 lb Drawbar pull)**



### Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights
- Modular lighting includes: Tail/Stop Lights, Back-up Light & Turn Signals
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat
- Dual drive wheels
- Driver hitch release

**Specifications subject to improvement and/or change without notice**

# Specifications for Model: STREAMLINE CARGO MASTER (8k) Towing Tractor

## Drawbar Pull Available

<u>Model</u>	<u>DBP</u>	<u>(+/-) GVW</u>	<u>(+/-) Towed Wt</u>
HTLP80.....	8,000 lbs	.....9,600 lbs	..... 80,000 lbs
Towed weight on a dry surface up to a 3% grade			

## Dimensions

Length.....	117" (2972 mm)
Width.....	67" (1702 mm)
Height.....	61" (1549 mm)
Height w/cab.....	81" (2070 mm)
Wheel Base.....	70" (1778 mm)
Ground Clearance.....	6" (152 mm)

## Available Diesel Engines (turbo-charged) Equipped with Gauge & Sender system

- *Cummins*
- *Perkins*

### **Transmission**

- Ford C-6 Automatic
- 3-speeds forward, 1 reverse

### **Electrical**

- 12 V, Negative ground

### **Cooling System**

- Dual core cross-flow radiator with 3.75 quart capacity
- Oil cooled radiator with the Deutz engine

### **Steering System**

- Hydraulic steering (Saginaw power assisted)

### **Turning Radius**

- 135" (3429mm)

### **Drive Axle**

- Heavy duty Harlan--10,000 lb Capacity

### **Steer Axle**

- Heavy duty Harlan with 1 1/8" King Pin

### **Suspension**

- Shocks & Leaf Springs on front and rear axles

### **Brakes**

#### **Service:**

- Dual Split System
- Hydraulic/Hydraulic
- Dual rear disc with front disc brakes
- Other brake options available upon request

#### **Parking:**

- Mechanical Drum (lever activated)

### **Towing Coupler**

- Front & Rear Three-tier hitch – 1 3/4" pin
- Other couplers available on request

### **Tires**

- Front: 6.50 x 10
- Dual Rear Wheels: LT215/80R x16