

GSE Towing Tractor TT-10

Main Specifications

Engine: DEUTZ 4 cylinders diesel engine
103/2500rpm

Transmission: DANA, powershift w/torque converter
4 forward & 3 reverse

Max speed(empty): F: 25km/h, R: 20km/h

Axle: Front Dana Steering & Driving axle w/leaf
spring suspension, Rear DANA steering and
driving axle

Brake(service): MICO dual circuit, 4 wheel hydraulic
driving, oil brake w/ 2 accumulators

Brake(parking): Oil brake on 2 rear wheels hydraulically
actuated

Steering: Front wheel steering, rear wheel steering,
4 wheel hydraulic paver steering

Tow hitch: Front & rear with 70mm diameter tow pin,
Manually controlled

Tyre: 8.25-15

Fuel tank: 100L

Hydraulic tank : 80L

Cab w/o door: Suspended driver seat, standard seat for
passenger

Paint: RAL 9016 white

Use for B717, 727, 737, 757, 767-200, A318, 319, 320, 321, 310, APJ21



Electrical Information:

24V DC electrical system equipped w/2x12v 90Ah battery.

55 A alternator,

Front head lights, rear lights, stop lights, turn signal lights, flashing lights, backup lights, warning lights

Hydraulic system: one hydraulic pump flanged on transmission PTO for power steering and braking

Driving station: Electrical horn; Ignition switch; Gauges hourmeter, transmission oil temperature, Fuel level; Indicator lights (brake oil coolant, batteries charge, engine oil pressure, engine water temperature, preheating, turn signal lights, head lights, parking brake indicator

Product Technical Parameters

Overall : 5720x2110x1960mm

Towing pin height: 480mm

Ground Clearance : 165mm

Towing pin length: 402mm

Mass towing weight: 150000kgs

Towing radius: 3220mm

Mass towing : 72kn

Drive at right side or drive at left side

Tare weight: 15300kg

Wheelbase: 2200mm

Front track: 1790mm

Rear track: 1790mm